

| Specification                   |                |
|---------------------------------|----------------|
| Product parameters              | HJC100         |
| Rated operating capacity(kg)    | 1200           |
| Tipping load(kg)                | 2400           |
| Bucket capacity(m³)             | 0.7            |
| Operationg weight(kg)           | 3560           |
| Max. travel speed(km/h)         | 12             |
| Hydraulic pump flow(L/min)      | 80/130         |
| Fuel tank capacity(L)           | 90             |
| Tires                           | 12/16.5NHS     |
| Overall dimensions(mm)          | 3700×1900×2150 |
| Height at maximum extension(mm) | 4070           |
| Height to bucket hinge pin(mm)  | 3150           |
| Width with bucket(mm)           | 1900           |
| Track width(mm)                 | 1500           |
| Wheelbase(mm)                   | 1185           |
| Ground clearance(mm)            | 260            |
|                                 |                |

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| Dump angle         | 40°                                                      |
| Dumping height(mm) | 2450                                                     |
| Maximum reach(mm)  | 710                                                      |
| Rollback at ground | 26°                                                      |
| Angle of departure | 20°                                                      |
| Maker/Model        | WEICHAI                                                  |
| Net power          | 75KW/2500rpm                                             |
| Type               | 4Cylinder in-line, Water cooled, 4 stroke, Diesel engine |
| Displacement(L)    | 4.1                                                      |